


## JS14-S Series Time Relay



### 1 Product overview

JS14-S series time relay is used in the AC 50Hz control circuit with rated control power voltage up to 380V or with DC 24V as delay element for turn on or turn off circuits as scheduled.

### 2 Type designation




### 3 Product parameters

Working mode	Power-on delay
Number of contacts	Delay 2 change-over
Contact capacity	5 A 220VAC (resistive) U <sub>e</sub> /I <sub>e</sub> : AC-15 220V/0.5A; DC-13 24V/0.5A; I <sub>th</sub> : 5A
Power voltage	AC50Hz 36V、110V、127V、220V、380V、DC24V (other voltage can be customized)
Electrical life	1 × 10 <sup>5</sup> times
Mechanical life	1 × 10 <sup>6</sup> times
Delay accuracy	≤1%
Ambient temperature	- 5 °C ~ +40°C
Installation method	Panel-type

Model	Delay range
JS14-S	0.1s~9.9s, 1s~99s, 0.1min~9.9min, 1min~99min, 0.1h~9.9h, 1h~99h, 0.01s~9.99s,
JS14-S1	0.1s~99.9s, 1s~999s, 1s~9min59s, 0.1min~99.9min, 1min~999min, 1min~9h59min,
	0.1h~99.9h, 1h~999h, 0.01s~99.99s, 0.1s~999.9s, 1s~9999s, 0.1min~999.9min,
	1min~99h59min, 1s~99min59s, 1min~9999min, 0.1h~999.9h, 1h~9999h

## JS14-S Series Time Relay

### 4 Wiring diagram



### 5 Outline and installation dimensions

